

ATH Comfort Lift 2.40XL

Product Images



Description

- Electro-hydraulic 2-post lift with quick lift unit and load-dependent lowering function
- Two control units for flexible use on both columns
- Energy set (230V / compressed air / 12V) on the main post
- Safety Control: Electromagnetic safety locks that automatically unlock with lifting and lowering
- Safety Lock: ability to lock the load on to the safety mechanism
- Multifunctional mounting via 3-part support arms and double telescopic support plates
- **Top-running crossbar with variable height adjustment**

Additional Information

| | |
|-----------------------|------------------------------------|
| Rated load capacity | 4.000 kg |
| Lifting height max. | 2.000 mm |
| Drive-through width | 2.500 mm |
| Overall width | 3.542 mm |
| Overall height | 4.280 mm |
| Support arms parts | 3 |
| Driving power | 3 kW |
| Lifting/Lowering time | ca. 30 s |
| Power supply voltage | 3x 400V / C16A |
| Concrete strength | min. C20/25 4.000 x 2.000 x 220 mm |



ATH W42 LED 3D

Product Images



Description

- Automatic distance, rim diameter and rim width (3D function) measurement
- Operation via ergonomically arranged front control panel, large shelf with numerous compartments
- Digital and optical position display of the weights via LED monitor and duo laser (LPS) 12/6 o'clock
- Static / dynamic, ALU programs, ALU weight optimization and back spoke placement
- Quick-release nut clamping with 40 mm shaft diameter, easy attachment of the weights via pedal-operated parking brake and measuring tool, integrated interior wheel lighting
- Wheel protection with automatic start-stop function
- Precise work thanks to the latest microprocessor control
- Ideally suited for car wheels, with optional accessories also for motorcycle and light truck wheels

Additional Information

| | |
|--------------------------|-------------|
| Center hole diameter rim | 45 – 130 mm |
| Measurement tolerance | ± 1 g |
| Measuring time | 7 s |
| Measuring speed | 180 U/min |
| Rim width | 1,5 – 20 " |
| Rim diameter | 12 – 24 " |
| Max. wheel diameter | 900 mm |
| Wheel weight max. | 65 kg |
| Driving power | 0,25 kW |
| Power supply voltage | 230V / C16A |



ATH M72 + A34

Product Images



Description

- Rear swivel with pneumatic mounting head clamping including automatic vertical and horizontal Rim removal
- Control via ergonomically arranged foot pedals
- Including pneumatic controlled auxiliary assembly arm ATH A34 for effortless and damage-free assembly of low profile, UHP and run-flat tires
- Self-centering, pre-adjustable 4-jaw system with two double-acting aluminium clamping cylinders; Outside clamping range up to 26 ", 3-fold quick adjustment
- Lateral extractor with double-acting aluminium cylinder and anti-jamming system
- Ideally suited for car tires, with optional accessories also for motorcycle bikes

Additional Information

| | |
|------------------------------|----------------------|
| Clamping range inner / outer | 11 – 30 " / 9 – 26 " |
| Rim width | 4 – 13 " |
| Max. wheel diameter | 1.050 mm |
| Compressed air connection | 10 bar |
| Bead breaking range | 83 – 350 mm |
| Bead breaker force | 2.500 kg |
| Mounting speeds | 6 and 12 U/min |
| Driving power | 0,75 / 0,90 kW |
| Power supply voltage | 3x 400V / C16A |
| Noise level | 70 dB(A) |

